

eSmart3 MPPT 12/24/36 / 48V 20A 30A 40A 50A 60A [mppt](#)

NEW

iPaidea

MPPT Solar Charge Controller
Adopting Advanced MPPT Technology
High Conversion Efficiency
RS485 Port

MPPT SOLAR CONTROLLER
C Mode
27.4V
SELECT CONFIRM

MPPT Solar Controller
12V24V36V48V 20A-40A

CE FCC

FEDERAL COMMUNICATIONS COMMISSION
USA

RoHS

NEW



MPPT Solar Controller 12V24V36V48V 20A-40A



















- 1. MPPT效率 ≥ 99.5%
- 2. 转换效率高
- 3. 支持多路PV输入
- 4. 支持多路负载
- 5. 支持Seal \ Gel \ Flooded
- 6. 支持PV输入
- 7. 支持RS485
- 8. 支持WiFi APP
- 9. CE \ RoHS \ FCC
- 10. 支持2路10A

MPPT










Off Grid Solar System CPU



□□□□□□□□



LCD□□□□



On	Mean "ON"	FLD	Mean "FLD"
OFF	Mean "OFF"	GEL	Mean "GEL"
USER	Mean "USER"	SEL	Mean "SEL"

□□□□□□ □□□□ □□

□□□□□□□□□□

□□□□	□□□□	□□□□□□□□□□	
	□□□□	□□□□□□□□□□□□□□	
	□□□□	-20°C□+ 50°C	
	□□□□	-40°C□+ 75°C	
	IP□□□□□□	IP21	
	□□□□□□	20□□□□	30□□□□
	□□□□□□	2.3	2.6
	□□□□kg□	3	3.5
	□□□□mm□	240 * 168 * 66	270 * 180 * 85
	□□□□mm□	289 * 204 * 101	324 * 223 * 135