#### Introduction:

This is a smart solar charge controller which has advanced MPPT technology .<u>Solar charge controller</u> is one of the important parts in the off-grid solar system. For having the advanced MPPT technology, the controller can trace the peak power with 99% conversion efficiency. MPPT microprocessor, inside the controller making 30% more charge current with significantly less power than tradition. In addition to this, easier installing and supporting to expand volume are other advantages. It can also store energy to different kinds of batteries. We provide battery choice(Vented Sealed Gel NiCd).



#### Feature:

- 1.MPPT charge mode, conversion efficiency upto 99%, can save 30%~60% of the power than traditional controller.
- 2. With high efficient MPPT operation scheme and adopting TI28035 chip, make the Solar panels utilization rate upto 99%.

Intelligent design, the device can be upgraded online, customers enjoy the lifelong upgrade service.

- 4.Compliance with the 2002/95/EC environment protecting demand, doesn't include the Cadmium, hydride and fluoride
- 5.Adopting the well-known brand components,the devices can suffer the temperature not less than  $105\,^{\circ}$ C. The service life is designed to extend to 10 years in theory.
- 6. Charge mode: three stages (fast charge, constant charge, floating charge)
- 7.12V/24V/48V system auto recognize for easy control.
- 8. Nominal maximum solar input is DC 150V
- 9.Connected Battery Type choosing: Sealed lead acid, vented, Gel, NiCd battery. Other types of the batteries can also be defined.
- 10. LCD and LEDs show all kinds of parameter like products model, PV input voltage,battery voltage,charge current,charge power,work condition,and also can add customers' company name and website.
- 11. Communication Port.RS232 communication can provide communication protocol, This make the unified and integrated management more convenient to customers.

- 12. With providing a Microsoft by connecting with PC that can show the working state and all parameters in 7 languages.
- 13. Extensible LAN remote control.
- 14.Equipment integrity: controller+CD-ROM(microcomputer software) + communication wire+Anderson terminals;
- 15.CE,ROHS,FCC,PSE certifications approved. The device also can support to pass the other certifications.
- 16. 2 years warranty. And 3~10 years extended warranty service also can be provided.





## **Parameters:**

Model:I-P-SMART1-DC12V/24V/48V-series	40A	
Charge Mode	Maximum Power Point Tracking	
Method	3 stages: fast charge(MPPT),constant voltage,floating charge	
System Type	DC12V/24V/48V	Automatic recognition
System Voltage	12V system	DC9V~DC15V
	24V system	DC18V~DC30V
	48Vsystem	DC36V~DC60V
Soft Start Time	12V/24V/48Vsystem	≤105
Dynamic Response Recovery Time	12V/24V/48Vsystem	500us
Conversion Efficiency	12V/24V/48Vsystem	≥96.5%,≤99%
PV Modules Utilization Rate	12V/24V/48Vsystem	≥99%
Input Characteristics		
	12V system	DC18V~DC150V
MPPT Working Voltage and Range	24V system	DC34~DC150V
	48V system	DC65~DC150V
	12V system	DC16V
Low Voltage Input Protection Point	24V system	DC30V
	48V system	DC60V
Low Voltage Input Recovery Point	12V system	DC22V
Low voltage input Recovery Point	24V system	DC34V
	48V system	DC65V
Max DC Voltage	12V/24V/48V system	DC160V
Input Overvoltage Protection Point	12V/24V/48V system	DC150V
Input Overvoltage Recovery Point	12V/24V/48V system	DC145V
Max. PV Power	12V system	570W
	24V system	1130W
	48V system	2270W
Output Characteristics		
Selectable Battery Types (Default type is GEL battery)	12V/24V/48Vsystem	Sealed lead acid, vented, Gel, NiCd battery (Other types of the batteries also can be defined)
Constant Voltage Floating Charge Voltage	12V/24V/48V system 12V/24V/48V system	Please check the charge voltage according to the battery type form.

Over Charge Protection Voltage	12V system	14.6V
	24V system	29.2V
	48V system	58.4V
Rated Output Current	12V/24V/48V system	40A
Current-limiting Protection	12V/24V/48V system	44A
Temperature Factor	12V/24V/48V system	±0.02%/°C
Temperature Compensation	12V/24V/48V system	14.2V-(The highest temperature-25°C)*0.3
Output Ripples(peak)	12V/24V/48V system	200mV
Output Voltage Stability Precision	12V/24V/48V system	≤±1.5%

### **Pictures:**









The Figures of the PC Firmware and Testing Software




Figure 1: PC Firmware




Figure: Testing Software

Welcome to order I-Panda MPPT Solar Charge Controller Smart1 48V 40A~60A



# **Company**











shipping way

