


12/24V auto work mppt charge controller, Backlight LCD display+dual USB 5V 3A



WISER series adopted with auto cool, high conversion efficiency, LCD display and free PC software. It features an efficient [MPPT controller](#) algorithm to track the maximum power point of the PV array in any environment. Greatly improve the utilization of solar panel. Also added the output function(USB 5V 3A). For the mppt controller can be widely used in off-grid solar system, Communication base station solar system, household solar systems, street light solar systems, field monitoring and other fields.




Features
















- 1.It has an efficient MPPT algorithm, MPPT efficiency $\geq 99.5\%$ and converter efficiency up to 98%
- 2.Charge mode: three stages (constant current, constant voltage, floating charge), it prolongs service life of the batteries.
- 3.Four types of load mode selection: ON/OFF, PV voltage control, Dual Time control, PV+Time control .
- 4.Battery system voltage automatic recognition.
- 5.Three kinds of commonly used lead-acid battery (Seal\Gel\Flooded) parameter settings can be selected by the user, and also self-defined the parameters for other battery.
- 6.Natural cooling design is adopted to improve the reliability of the product and prolong the service life of the product.
- 7.The input and output of all kinds of protection functions are complete to protect the system.
- 8.The use of high strength plastic shell design makes the shape beautiful, and the effective reduction of the product weight can save the transportation cost.
- 9.Equipped with 5V3A USB dual output power supply function, support mobile phone and tablet charging products etc..

10. It has a current limiting charging function. When the power of PV is too large, the controller automatically keeps its rated charging power, and the charging current will not exceed the rated value.
11. High definition LCD display function to check the device running data and working status, also can support modify the controller display parameter.
12. RS485 communication, we can offer communication protocol to convenient user's integrated management and secondary development.
13. Support PC software monitoring and WiFi module to realize APP cloud monitoring.
14. CE, RoHS, FCC certifications approved, we can assist clients to pass various certifications.
15. Three years warranty, and 3~10 years extended warranty service also can be provided.















MPPT Controller connection diagram



Parameters Display & Setting information




LCD display information



On	Mean "ON"	FLD	Mean "FLD"
OFF	Mean "OFF"	GEL	Mean "GEL"
USER	Mean "USER"	SEL	Mean "SEL"

Set the battery type and LOAD control mode

Upper Computer Software and Test Software



PC software_SolarEagle

Visual display of charge and discharge status, PV voltage, charge voltage, charge current, and can set the battery type, LOAD output control;

Parameter

WISER3-series	WISER3 -15A	WISER3 -20A	WISER3 -30A	WISER3 -40A	WISER3 -50A	
Product category	Controller Properties					
	MPPT (maximum power point tracking)					
	MPPT efficiency $\geq 99.5\%$					
	Standby power 0.5W~1.2W					
	System voltage Automatic recognition					
Input Characteristics	Heat-dissipating method Intelligent fan cooling					
	Max.PV input voltage(VOC) DC100V		DC150V			
	Start the charge voltage point Battery voltage + 3V					
	Low input voltage protection point Battery voltage + 2V					
	Over voltage protection point DC100V		DC150V			
Charge Characteristics	Rated PV 12V system	195W	260W	390W	520W	
	power 24V system	390W	520W	780W	1040W	
	Battery Types options (Default Gel battery) Sealed lead acid, Gel battery, Flooded (Other types of the batteries also can be defined)					
	Charge rated current	15A	20A	30A	40A	50A
	Charging Method	3-Stage: constant current(fast charging)-constant voltage-floating charge				
LOAD Characteristics	Load voltage	The same as the battery voltage				
	Load rated current	20A		50A		
Display &	Load control mode	On/Off mode, PV voltage control mode, Dual-time control mode, PV + Time control mode				
	Display mode	High-definition LCD segment code backlight display				
Communication	RS485/support PC software monitoring/					
	Communication mode	support WiFi module to realize APP cloud monitoring				

Other Parameters	Protect function	Input-output over \ under voltage protection, Prevention of connection reverse protection,battery shedding protection etc.	
	Operation Temperature	-20°C~+50°C	
	Storage Temperature	-40°C~+75°C	
	IP(Ingress protection)	IP43	
	Max. connection size	12mm ²	30mm ²
	Net Weight (kg)	0.83	1.65
	Gross Weight (kg)	1	1.95