









- 1.000950-9900000000000
- 2.00000030000000000
- 3.0000000
- 4.



<u>mppt</u>

□□□I-P-SMART1 -DC12V / 2	24\/ / 48\/□□	40A	50A	60A
		70/1	J0A	OUA
	30000000			
	DC12V / 24V / 48V			
	12V□□	DC9V[DC15V		
	24V	DC18VDC30V		
	48V□□	DC36V□DC60V		
	12V / 24V / 48V□□	≤10S		
	12V / 24V / 48V□□	500us		
	12V / 24V / 48V□□	≥96.5[[]≤99[]		
	12V / 24V / 48V□□	≥99[]		
	12V[[DC18VDC150V		
MPPT	24V[[DC34[DC150V		
	48V <u>□</u> □	DC65[DC150V		
	12V[[DC16V		
00000000	24V□□	DC30V		
	48V <u>□</u>	DC60V		
	12V	DC22V		
	24V□□	DC34V		
	48V∏∏	DC65V		
	12V / 24V / 48V∏∏	DC160V		
	12V / 24V / 48V□□	DC150		
	12V / 24V / 48V	DC145V		
	12V / 24V / 40V	570W	700W	900W
	24V	1130W	1400W	1700W
	48V[[2270W	2800W	3400W
		NiCd	lΠ	
	12V / 24V / 48V□□		JL	
	12V / 24V / 48V□□			
	12V / 24V / 48V□□]	
	12V / 24V / 46V	14.6V		
	24v	29.2V		
		58.4V		
	48V□□		Γ Λ Λ	
	12V / 24V / 48V	40A	50A	60A
	12V / 24V / 48V□□	44A	55A	66A
	12V / 24V / 48V□□	±0.02∏/°C	·····	
	12V / 24V / 48V	14.2V-[[[[[[[]]]]-25°C[]* 0.3	
	12V / 24V / 48V□□	200mV		
	12V / 24V / 48V□□	≤±1.5[]		
00				
LED[][]		30LED00000000000000		
		RS232		
		00000		
0000000				
		95℃		
			1ППЗАП	
		-		
		≤40dB		
			100000000000000000000000000000000000000	
			JUU	
		00000000000000000000000000000000000000	05°C	
İ		000000000000000001	LUJ C	

	2002/95 / EC
□□DxWxH□mm□	270 * 185 * 90
N.G∏kg∏	3
G.N∏kg∏	3.6
	0/0000
	CE[]RoHS[]PSE[]FCC
EMC	EN61000
	IP21
00	
	0 <u>0</u> 90 <u>0</u> RH <u>0</u> 000
	0∏3000m
	-20°C <u>□</u> + 40°C
	-40°C□+ 75°C
	70∏106kPa

1	1[[0000
2	2 pc	
3	2 pc	
4	4□	
		00000000000
5	1 pc	232 R 45
6	1 pc	
7	1 pc	
8	2 pc	000