[illegible]

[illegible]DC / AC[illegible] [illegible]·[illegible][illegible] [illegible]AVR[illegible]AC[illegible] UPS [illegible]IP-XD[illegible]

[illegible]

1[illegible]

[illegible]2[illegible]CPU[illegible]

[illegible]3[illegible]LCD[illegible]

4[illegible]AVR[illegible]UPS[illegible]

5[illegible]

6[illegible]

[illegible]7[illegible]5[illegible]

8[illegible]

9[illegible]CE / EMC / LVD / RoHS[illegible]

10[illegible]

[illegible]

[illegible]		500VA
[illegible]		350W
[illegible]		700W
[illegible]DC[illegible]		12V / 24V[illegible]
[illegible]W×D×H[illegible]mm[illegible]		335 * 165 * 375
[illegible]W×D×H[illegible]mm[illegible]		355 * 185 * 395
[illegible]kg[illegible]		7
[illegible]kg[illegible]		8
[illegible]		
[illegible]	1	[illegible]AC [illegible]
[illegible]	2	[illegible] [illegible]5[illegible] [illegible]
	3	[illegible]1[illegible] [illegible]UPS[illegible]
AC[illegible]	[illegible]	220V[illegible]35[illegible]110V + 35[illegible]±
	[illegible]	3[illegible]60Hz±3[illegible]±50Hz[illegible]
AC[illegible]	[illegible]	220V±3[illegible]230V±3[illegible] 240V±3[illegible]100V±3[illegible]110V±3[illegible]
	[illegible]	0.5[illegible]60Hz±0.5±50Hz[illegible] [illegible]
[illegible]	AC[illegible]	0[illegible]15A
	[illegible]	[illegible] [illegible]
	[illegible]	[illegible] [illegible]

ディスプレイ	表示モード	LCD
	表示情報	入力電圧、出力電圧、出力 頻度、バッテリー 容量、負荷条件、ステータス 情報
出力波形タイプ		純粋な正弦波出力、合計 高調波歪みTHD≤3
過負荷能力		> 120%1分、> 130%の10S
消費電力	スリープモード	1~6W
	通常モード	1~3A
変換効率		~90%、80%
転送時間		<5msの（DC / DCへのACにAC）
保護		過負荷、短絡、ハイ 過熱入力電圧、低入力電圧、
環境	温度	-10℃~50℃
	湿度	~90%、10%
	標高	≤4000m