

☐☐



☐☐

- 1. MPPT
- 2.
- 3. [3](#)
- 4. PC

☐☐

- 1. MPPT 99%
- MPPT 2. With TI28035 99%
- 2002/95 / EC 4. Compliance
- 5. Adopting 105°C. the 10

☐☐

- 6. Charge 3
- 7. 12V / 24V / 48V
- 8. Nominal 150V
- 9. Connected
- 10. LCD LED PV customers' company

11. Port.RS232

7 PC 12

13. LAN

14. Equipment + CD-ROM + +

15. CE ROHS FCC PSE approved. The

16. 2 3 10

Specifications

P-MSC-DC12V / 24V / 48V		50A
MPPT	3	
DC12V / 24V / 48V	DC9V DC15V	
24V	DC18V DC30V	
48Vsystem	DC36V DC60V	
12V / 24V / 48Vsystem	≤10S	
12V / 24V / 48Vsystem	500US	
12V / 24V / 48Vsystem	≥96.5 ≤99	
PV	12V / 24V / 48Vsystem ≥99	
MPPT	12V	DC18V DC150V
24V	DC34 DC150V	
48V	DC65 DC150V	
12V	DC16V	
24V	DC30V	
48V	DC60V	
12V	DC22V	
24V	DC34V	
48V	DC65V	
12V / 24V / 48V	DC160V	
12V / 24V / 48V	DC150V	
12V / 24V / 48V	DC145V	
12V	700W	
24V	1400W	
48V	2800 W	
12V / 24V / 48Vsystem		
12V / 24V / 48V		
12V / 24V / 48V		
12V	14.6V	
24V	29.2V	
48V	58.4V	
12V / 24V / 48V	50A	
12V / 24V / 48V	55A	
12V / 24V / 48V	±0.02/°C	
12V / 24V / 48V	14.2V-25°C* 0.3	
12V / 24V / 48V	200mV	
12V / 24V / 48V	≤±1.5	
LCD		
LED	3	
PC	RS232 LAN	
95°C		
85°C	3A	

噪音	≤40dB
重量	3.6kg
尺寸	270 * 185 * 90 mm
工作温度	-20°C ~ +40°C
存储温度	-40°C ~ +75°C
湿度	0 ~ 90% RH
压力	70 ~ 106 kPa
认证	CE, RoHS, EN61000
其他	IP21

支持 OEM 及 ODM 服务。The 36V / 72V / 96V

支持定制

