

	12V/24V/48V	DC150	
	96Vsystem	DC300V	
	12V/24V/48V	DC145V	
	96Vsystem	DC295V	
	12V	280W	450W
	24V	560W	850W
	48V	1120W	1700W
	96Vsystem	2240W	3400W

品質保証

	12V/24V/48V/96Vsystem	NiCd	
	12V/24V/48V/96Vsystem		
	12V/24V/48V/96Vsystem		
	12V	14.6V	
	24V	29.2V	
	48V	58.4V	
	96V	116.8V	
	12V/24V/48V/96Vsystem	20A	30A
	12V/24V/48V/96Vsystem	25A	35A
	12V/24V/48V/96Vsystem	0.02°C±	
	12V/24V/48V/96Vsystem	14.2V-25°C* 0.3	
	12V/24V/48V/96Vsystem	200mV	
	12V/24V/48V/96Vsystem	≤±1.5	

付属品

LCD	LCD		
LED	3LED		
	RS232 LAN		

環境適合

温度	95°C
湿度	85°C 3A

その他

	≤40
	RAN
	EU 105°C

□□□□	2002/95/EC□□□□□□□□□□□□□□□□□□
□□□□	
□□DxWxH□MM□	270 * 185 * 90
N.G□KG□	3
G.N□KG□	3.6
□□□	□□□/□□□□□□□□□□□□
□□	CE□RoHS□□□PSE□FCC
EMC	EN61000
□□□□□□□□	IP21
□□	
□□	0□90□RH□□□□□□□□□□
□□	0□3000□□□□□□
□□□□	-20°C□+40°C
□□□□	-40°C□+75°C
□□	70□106kPa□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□OEM□ODM□□□□□□□□□□□□□□□□ 36V/72V/96V□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□



PC□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□