

一、

- 1.MPPT充電器99種類可供選擇
- 2.12V / 24V / 48V可供選擇 max PV 150V
- 3.Wide DC150V
- 4.Journal
- 5.Charge 3種類可供選擇。It
- 6.Discharge PV PV
- 7.Recommended NiCd
- 8.Most LCD LED PV
- 9.RS232 LAN IP area. And
- 10.11.
- 11.With
- 12.Adopting 105°C.the
- 13.Compliance 2002 95/EC
- 14.Equipment CD-ROM
- 15.CE ROHS
- 16.2種類可供選擇3種類可供選擇

二、

MODEL	SMART2-20A / 25A / 30A - SERIES	20A	25A	30A
MPPT	12V	DC18V DC150V		
	24V	DC34 DC150V		
	48V	DC65 DC150V		
MPPT	12V	DC16V		
	24V	DC30V		
	48V	DC60V		
MPPT	12V	DC22V		
	24V	DC34V		
	48V	DC65V		
DC		DC160V		
		DC150		
		DC145V		
PV	12V	286W	357W	429W
	24V	572W	715W	858W
	48V	1144W	1430W	1716W
MPPT	NiCd GEL			
MPPT	DC10V DC15V			
MPPT	12V 12V			
MPPT	12V / 24V / 48V SYS			
MPPT	12V / 24V / 48V SYS			
MPPT	20A	25A	30A	
MPPT	25A	30A	35A	
MPPT	±0.02%/°C			
MPPT	14.2V-25°C * 0.3			
MPPT	200mV			
MPPT	≤±1.5%			
MPPT	200mV			
MPPT	≤±1.5%			

LAN	LAN
30A	30A
420W	840W
40A×2	40A×2
ON / OFF	ON / OFF
PV	PV/PV
PV/	PV
10.5	10.5; 1
COM	
RS232	COM
LAN	IP· ; TCP
	95°C
	85°C 3A
	≤40dB
	EU ;
	2002/95 / EC substances.All 105°C
PHYSICAL	
DxWxH mm	270 * 185 * 90
N.G kg	2.1
G.N kg	2.4
EMC	EN61000
	IP21
	0~90RH
	0~3000
	-20°C~+ 40°C
	-40°C~+ 75°C
	70~106kPa

OEM ODM service.The 36V / 72V / 96V

www.



Blue



Green




Upper Computer




Package

NO.	Quantity	Description
1	1 pc	Charge controller
2	2 pc	Gallow pulley (For install the controller on the wall)
3	4 set	Screw (For install the controller on the wall)
4	1 pc	232 turn to RJ45 communication cable
5	1 pc	User manual
6	1 pc	Temperature sensing wire
7	2 pc	Fuse wire

.....




The interface of upper computer software working state



The interface of upper computer software parameter setting state



Upper computer software on/off interface and generating capacity record clean interface



The interface of test software working state

□

1. 100W 12V 20A MPPT charge controller with RS485 communication

2. 100W 12V 20A MPPT charge controller with RS485 communication and CD administrator. More than 100W 12V 20A MPPT charge controllers are available.

3. WIN7 or WIN8 operating system required for I-Panda software.

4. 100W 12V 20A MPPT charge controller can be controlled by I-Panda software.




□

1. 100W 12V 20A MPPT charge controller with RS485 communication and CD administrator. More than 100W 12V 20A MPPT charge controllers are available.

2. 100W 12V 20A MPPT charge controller with RS485 communication and CD administrator. More than 100W 12V 20A MPPT charge controllers are available.

□



□□

1□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

2□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□