

RS 232 / LAN
 PV
 IP-TPI2
 UPS

1. 2. 3. 4. 5. 6.

1. 2. 3. 4. 5. 6.

1. 2. 3. 4.

1. 30-60
1. 99
2. 3
2. 4 DC
3. RS232
4. 1 100

1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 12. 13. 14. 15. 16.

1. MPPT 99
2. 12V / 24V / 48V
3. DC150V
- 4.
- 5.
6. Charge 3 .It
7. Discharge / OFF PV + ON
8. Recommended NiCd
9. Most LCD LED PV
10. RS232 LAN IP area. And
- 11.
12. With
13. Adopting 105°C. The 10
14. Compliance 2002/95 / EC
15. Equipment + CD-ROM + + + ;
16. CE ROHS

40A 50A 60A

| | 40A | 50A | 60A |
|-----------------------|-----------------------|-------|------|
| MPPT | 3 MPPT | | |
| DC | DC12V / 24V / 48V | | |
| 12V | DC9V | DC15V | |
| 24V | DC18V | DC30V | |
| 48Vsystem | DC36V | DC60V | |
| 12V / 24V / 48Vsystem | ≤10S | | |
| 12V / 24V / 48Vsystem | 500US | | |
| 12V / 24V / 48Vsystem | ≥96.5% ≤99% | | |
| PV | 12V / 24V / 48Vsystem | | ≥99% |

| | | | |
|-----|--------------|-----|-----|
| CE | RoHS | PSE | FCC |
| EMC | EN61000 | | |
| IP | IP21 | | |
| 0 | 90 | RH | |
| 0 | 3000 | | |
| | -20°C + 40°C | | |
| | -40°C + 75°C | | |
| | 70 106kPa | | |

OEM ODM 36V / 72V / 96V

| NO | | |
|----|------|----------|
| 1 | 1 | |
| 2 | 2 PC | |
| 3 | 2 PC | Gallow |
| 4 | 4 | |
| 5 | 1 | RJ45 232 |
| 6 | 1 | |
| 7 | 1 | |
| 8 | 2 PC | |



Blue



Green



Upper Computer Software



Parts



Package

MPPT



