


## 12/24V auto work mppt charge controller, Backlight LCD display+dual USB 5V 3A



WISER series adopted with auto cool, high conversion efficiency, LCD display and free PC software. It features an efficient [MPPT controller](#) algorithm to track the maximum power point of the PV array in any environment. Greatly improve the utilization of solar panel. Also added the output function(USB 5V 3A). For the mppt controller can be widely used in off-grid solar system, Communication base station solar system, household solar systems, street light solar systems, field monitoring and other fields.




## Features

















- 1.It has an efficient MPPT algorithm, MPPT efficiency  $\geq 99.5\%$  and converter efficiency up to 98%
- 2.Charge mode: three stages (constant current, constant voltage, floating charge), it prolongs service life of the batteries.
- 3.Four types of load mode selection: ON/OFF, PV voltage control, Dual Time control, PV+Time control .
- 4.Battery system voltage automatic recognition.
- 5.Three kinds of commonly used lead-acid battery (Seal\Gel\Flooded) parameter settings can be selected by the user, and also self-defined the parameters for other battery.
- 6.Natural cooling design is adopted to improve the reliability of the product and prolong the service life of the product.
- 7.The input and output of all kinds of protection functions are complete to protect the system.
- 8.The use of high strength plastic shell design makes the shape beautiful, and the effective reduction of the product weight can save the transportation cost.
- 9.Equipped with 5V3A USB dual output power supply function, support mobile phone and tablet charging products etc..

- 10.It has a current limiting charging function. When the power of PV is too large, the controller automatically keeps its rated charging power, and the charging current will not exceed the rated value.
- 11.High definition LCD display function to check the device running data and working status, also can support modify the controller display parameter.
- 12.RS485 communication, we can offer communication protocol to convenient user's integrated management and secondary development.
- 13.Support PC software monitoring and WiFi module to realize APP cloud monitoring.
- 14.CE, RoHS, FCC certifications approved, we can assist clients to pass various certifications.
15. Three years warranty, and 3~10 years extended warranty service also can be provided.
















### **MPPT Controller connection diagram**



### **Parameters Display & Setting information**




LCD display information



On	Mean "ON"	FLD	Mean "FLD"
OFF	Mean "OFF"	GEL	Mean "GEL"
USER	Mean "USER"	SEL	Mean "SEL"

Set the battery type and LOAD control mode

## Upper Computer Software and Test Software



PC software\_SolarEagle

Visual display of charge and discharge status, PV voltage, charge voltage, charge current, and can set the battery type, LOAD output control;

## Parameter

WISER3-series			WISER3 -15A	WISER3 -20A	WISER3 -30A	WISER3 -40A	WISER3 -50A
Product category	Controller Properties		MPPT (maximum power point tracking)				
	MPPT efficiency		≥99.5%				
	Standby power		0.5W~1.2W				
	System voltage		Automatic recognition				
	Heat-dissipating method		Intelligent fan cooling				
Input Characteristics	Max.PV input voltage(VOC)		DC100V		DC150V		
	Start the charge voltage point		Battery voltage + 3V				
	Low input voltage protection point		Battery voltage + 2V				
	Over voltage protection point		DC100V		DC150V		
	Charge Characteristics	Rated PV power	12V system	195W	260W	390W	520W
		24V system	390W	520W	780W	1040W	1300W
Battery Types options (Default Gel battery)		Sealed lead acid, Gel battery, Flooded (Other types of the batteries also can be defined)					
Charge rated current		15A	20A	30A	40A	50A	
Charging Method		3-Stage: constant current(fast charging)-constant voltage-floating charge					
LOAD Characteristics	Load voltage		The same as the battery voltage				
	Load rated current		20A		50A		
	Load control mode		On\Off mode, PV voltage control mode, Dual-time control mode, PV + Time control mode				
Display &	Display mode		High-definition LCD segment code backlight display				
Communication			RS485/support PC software monitoring/				
	Communication mode		support WiFi module to realize APP cloud monitoring				

Other Parameters	Protect function	Input-output over \ under voltage protection, Prevention of connection reverse protection,battery shedding protection etc.	
	Operation Temperature	-20°C~+50°C	
	Storage Temperature	-40°C~+75°C	
	IP(Ingress protection)	IP43	
	Max. connection size	12mm <sup>2</sup>	30mm <sup>2</sup>
	Net Weight (kg)	0.83	1.65
	Gross Weight (kg)	1	1.95